

801 Light – 802 Sand – 804 Dark – 805 Carrara

806 Botticino Light – 808 Botticino Dark

PRODUCT SPECIFICATION

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
	305 X 610	MICRO BEVEL	SMOOTH	
	Package (m2)	Palette (m2)		
	9 x  = 1,674 m ² = 14 kg	96 x  = 160,75 m ² = 1.350 kg		

TECNICAL SPECIFICATION

	ICON	STANDARTS	SPECIFICATION
Surface treatment [UV]			Yes
Underlay		IXPE	1 mm
Total thickness		ISO24337	5 mm
Wear layer thickness		EN429	0,5 mm
Performance Classification		EN ISO 10874	Class 32 Commerciale medio traffico
Wear resistance IP method A		ISO 24338 procedure A	Class 32
Impact resistance		EN 13329:2006+A1:2008 Annex F	Class 34
Castor chair resistance		EN ISO 4918	Class 32
Effect of furniture leg		EN ISO 16581	Pass
Residential indentation		EN ISO 24343-1	Class 32
Resistance to staining		EN 438-2 +A1	Class 34
Anti-slip resistance		EN 13893	DS
Electrostatic behavior		1815:2016	Anti static floor covering
Floor heating system		Suitable	Max 27°
Antibacterial		ISO 22196	Antibacterial
Pet-friendly			Pass
Phthalate analysis		Inhouse Method	Phatalete Free
Formaldehyde emissions		EN 717-1:2004	E1
Fire Behavior		EN13501-1 EN 9239-1:2010	BFL-S1
Thermal resistance		EN 12667	0.296W[m.K]
VOC emissions		FloorScore CE	Certified
Light Fastness		EN ISO 105-B02:2014	>6