

801 Light – 802 Sand – 804 Dark – 805 Carrara 806 Botticino Light – 808 Botticino Dark

PRODUCT SPECIFICATION

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
	305 X 600	MICRO BEVEL	SMOOTH	
	Package (m2)	Palette (m2)		
	9 x  = 1,647 m ² = 14 kg	66 x  = 108,70 m ² = 924 kg		

TECNICAL SPECIFICATION

	ICON	STANDARTS	SPECIFICATION
Surface treatment [UV]			Yes
Underlay		IXPE	1mm (kg/m3 100)
Total thickness		EN 17539	5 mm
Wear layer thickness			0,5 mm
Dimensional Stability and Curl		EN 23999	≤0,15 mm. %1 ≤2 mm.
Class		EN ISO 10874	Class 23-31-32-33-34
Residual indentation		EN ISO 24343-1	Class 34
Wear resistance Method A		EN 24338	Class 34
Impact resistance (big ball)		EN 13329:2006+A1:2008 Annex F	Class 34
Castor chair resistance		EN ISO 4918	Class 34
Effect of furniture leg		ISO 16581, tested with foot type 0	Class 34
Resistance to staining		EN 438-2 +A1	Grade for group 1,2,3
Flexibility Categories		EN ISO 178:2019	Hight rigidity
Light Fastness		EN ISO 105-B02:2014	≥6
Slide resistance		TS EN 13893	DS
Fire Behavior		TS EN13501-1	BFL-S1
Thermal resistance		ISO 8302	0,0311 M2k/w
Thermal Conductivity		EN 12677	0,296 W (m.K)
Floor heating system		Suitable	Max 27°
Electrostatic behavior		EN1815:2016	Antistatic floor covering
Emission of Formaldehyde		EN 717-1:2004	E1
Antibacterial		ISO 22196	Pass
Phatalate analysis		Inhouse Method	Phatalate Free
VOC emissions		M1 Protocol of Nov.2017	Pass